





















Small Frame Millermatic® and Multimatic® Comparison

					
		Millermatic 142	Millermatic 211	Multimatic 215	Multimatic 220 AC/DC
PROCESS CAPABILITIES					
 MIG/flux-cored		■	■	■	■
 DC stick				■	■
 DC TIG				■	■
 AC TIG					■
 DC pulsed TIG					■
WELDING CAPABILITY					
Mild and stainless steel	Min Max	24 ga. 3/16 in.	24 ga. 3/8 in.	24 ga. 3/8 in.	24 ga. 3/8 in.
Aluminum	Min Max	18 ga. 14 ga.	18 ga. 3/8 in.	18 ga. 3/8 in.	24 ga. 3/8 in.
POWER					
Input power	V	120	120/240	120/240	120/240
Amperage range	A	30-140	30-230	20-230	20-230
FEATURES					
Auto-Set™		■	■	■	■
MVP™			■	■	■
Color LCD display				■	■
QuickTech™					■
Pro-Set™					■
TIG high-frequency starts					■
PRICING		\$	\$	\$\$	\$\$\$

Large Frame Millermatic® and Multimatic® Comparison

						
PROCESS CAPABILITIES		Multimatic 235	Millermatic 252	Millermatic 255	Multimatic 255	Millermatic 350P
	MIG/flux-cored	■	■	■	■	■
	Pulsed MIG			■	■	■
	DC stick	■			■ Includes 6010	
	DC TIG/pulsed TIG	■			■	
WELDING CAPABILITY						
Mild and stainless steel	Min	24 ga.	22 ga.	24 ga.	24 ga.	24 ga.
	Max	3/8 in.	1/2 in.	1/2 in.	1/2 in.	1/2 in.
Aluminum	Min	18 ga.	14 ga.	18 ga.	18 ga.	18 ga.
	Max	3/8 in.	3/8 in.	1/2 in.	1/2 in.	1/2 in.
POWER						
Input power	V	240 (204-276 V)	208/230 or 230/460/575	208/240	208-575	208/230/460 1- and 3-phase
Output - 60% duty cycle		22.5 V at 170 A	24 V at 200 A	25.5 V at 230 A	25.5 V at 230 A	32 V at 300 A
Amperage range	A	20-235	30-300	20-350	5-350	25-400
FEATURES						
12-inch wire spool		■	■	■	■	■
Auto-Set™		■		■	■	
Program memory settings				■	■	
Auto-Line™				■	■	
Easy to read and use color LCD display		■		■	■	
Detachable cart		■		■	■	
PRICING		\$\$	\$\$\$	\$\$\$	\$\$\$	\$\$\$\$